

Cameron Carbon

INCORPORATED

Activated Carbon
& Related Technology

P.O. Box 995 Havre de Grace MD 21078 USA

Toll Free: (800) 394-6844

Tel: +1 (410) 942-0240 • Fax: +1 (410) 942-0242

www.cameroncarbon.com • sales@cameroncarbon.com

CE-HG(S)

Cameron type CE-HG(S) is a high activity, chemically impregnated, coal based extruded (pelletized) activated carbon specifically developed for the chemisorption of mercury vapor. In addition to a high degree of activation and impregnation this product also offers excellent mechanical strength and a highly developed pore structure. It is, therefore, an ideal choice for applications that require the removal of mercury vapor from air or other carrier gases. Standard packaging is in 200/250 lb drums, 50 lb bags or 1,000 lb bulk bags.

Mesh Size	4 mm diameter pellet
Carbon Tetrachloride Activity ***	60% w/w minimum
Moisture Content	15% w/w maximum
Hardness Number	99 minimum
Apparent Density	0.52 — 0.55 g/mL
Impregnant Level	9% w/w minimum

(*** refers to base carbon prior to impregnation)

This information has been gathered from standard reference materials and/or test procedures and is believed to be true and accurate. It is offered solely for your consideration and verification. None of the information presented shall be construed as constituting a warranty or representation, expressed, written, or implied, for which we assume legal responsibility or that the information or goods described is fit for any particular use either alone or in combination with other goods or processes, or that its use does not conflict with existing patent rights. No license is granted to infringe on any patent rights or practice any patent invention.