

Cameron Carbon

INCORPORATED

Activated Carbon
& Related Technology

P.O. Box 995 Havre de Grace MD 21078 USA
Toll Free: (800) 394-6844
Tel: +1 (410) 942-0240 • Fax: +1 (410) 942-0242
www.cameroncarbon.com • sales@cameroncarbon.com

CE65

Cameron type CE65 is a high activity extruded activated carbon manufactured from a carefully selected grade of high quality coal. In addition to a very high degree of activation this product also offers excellent mechanical strength and a highly developed pore structure. It is, therefore, an ideal choice for most vapor phase applications, process gas purification, and solvent recovery. Standard packaging is in 200 lb drums, 50 lb bags or 1,000 lb bulk bags.

Mesh Size	4 mm diameter pellet
Carbon Tetrachloride Activity	65% w/w minimum
Moisture Content (as packed)	5% w/w maximum
Hardness Number	98 minimum
Apparent Density	0.48 g/mL minimum
Surface Area (N ₂ B.E.T. Method)	1,000 m ² /g minimum

This information has been gathered from standard reference materials and/or test procedures and is believed to be true and accurate. It is offered solely for your consideration and verification. None of the information presented shall be construed as constituting a warranty or representation, expressed, written, or implied, for which we assume legal responsibility or that the information or goods described is fit for any particular use either alone or in combination with other goods or processes, or that its use does not conflict with existing patent rights. No license is granted to infringe on any patent rights or practice any patent invention.