

Cameron Carbon

INCORPORATED

Activated Carbon
& Related Technology

P.O. Box 995 Havre de Grace MD 21078 USA
Toll Free: (800) 394-6844
Tel: +1 (410) 942-0240 • Fax: +1 (410) 942-0242
www.cameroncarbon.com • sales@cameroncarbon.com

CG-PH

Cameron type CG-PH is a high activity, chemically impregnated, coal based granular activated carbon specifically developed for the chemisorption of hydrogen sulfide but is also effective for many other acid gases and low molecular weight mercaptans. In addition to a high degree of activation and impregnation this product also offers excellent mechanical strength and a highly developed pore structure. It is, therefore, an ideal choice for sewage odor abatement systems. Standard packaging is in 200 lb/225 lb drums, 50 lb bags or 1,000 lb bulk bags.

Mesh Size	4x6, 4x8, 4x10, 6x12
Carbon Tetrachloride Activity ***	60% w/w minimum
H ₂ S Breakthrough Capacity	0.14 g H ₂ S/mL carbon minimum
Moisture Content ***	2% w/w maximum
Hardness Number	95 minimum
Apparent Density	0.53 — 0.57 g/mL
Iodine Number ***	1,000 mg/g minimum
Ash Content ***	8% w/w maximum

(*** refers to base carbon prior to impregnation)

This information has been gathered from standard reference materials and/or test procedures and is believed to be true and accurate. It is offered solely for your consideration and verification. None of the information presented shall be construed as constituting a warranty or representation, expressed, written, or implied, for which we assume legal responsibility or that the information or goods described is fit for any particular use either alone or in combination with other goods or processes, or that its use does not conflict with existing patent rights. No license is granted to infringe on any patent rights or practice any patent invention.